

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

Coldline CBT48-LT 47" Refrigerated Salad Bar with Cutting Board and Lighted Sneeze Guard



FEATURES

- 47" refrigerated salad bar / cold food table
- Stainless steel exterior and interior
- Keeps food at safe temperatures
- Self-closing doors with 90 F stay-open feature
- Adjustable heavy-duty PVC coated shelves
- 10" depth cutting board included
- Auto defrost
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Fits 4" and 6" deep standard food pans
- Hydro-Carbon R290 refrigerant
- Durable sneeze guard with LED lighting

Sneeze guard installation required. #8 1" Self Drilling Pan Washer Head screws (included)

- cETLus Listed
 - ETL Sanitation Listed
- Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	47 7/16"W x 29 1/2"D x 55 3/16"H
Interior Dimensions	43"W x 19 7/8"D x 25 3/4"H
Packaging Dimensions	50"W x 33"D x 68"H
Net Volume	14 cu. ft.
Unit Weight	302 lb.
Shipping Weight	397 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.9
Watts	504
Plug Type	NEMA 5-15P

COOLING

Temperature Range	33°F to 41°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/2

CONSTRUCTION

Exterior Material	Stainless Steel
Interior Material	Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	(2) Qty: 20 13/16"W x 17 1/8"D
Shelf Load Capacity	90 lb.
Shelf Material	Epoxy Coated Steel
Adjustable Shelf	Yes
Pan Capacity	(9) x 1/3 or (18) x 1/6
Interior Light	No
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: CBT48-LT

MFR ITEM #: CBT-48



NEMA 5-15P

